



Open X Deluxe (N)

with sliding seat

Model	Item no.
Polyamide base black, with sliding seat	
without armrests	OX20W0
with armrests „TW1“, item no. 7111	OX20WTW1
with armrests „TW2“, item no. 7157	OX20WTW2
with armrests „TW3“, item no. 7161	OX20WTW3
Aluminum base polished, with sliding seat	
without armrests	OX29W0
with armrests „TW1“, item no. 7111	OX29WTW1
with armrests „TW2“, item no. 7157	OX29WTW2
with armrests „TW3“, item no. 7161	OX29WTW3
OPTIONS Hard floor castors big, item no. 6990 / Foot glides high, item no. 6990-2	

Fabrics

Seat: fabric group T (100% Trevira CS)
Backrest: mesh B50 black or B53 white

Seat: fabric group BJ (100% polyester)
Backrest: mesh B50 black or B53 white

Dimensions


Seat height: 42-57 cm
Seat width: 47 cm
Seat depth: 47 cm
Backrest height: 58 cm
Total height: 106-128 cm
Total depth: 56 cm

Technical data

Weight: approx. 18,2 kg
Unit: 1/carton
Pallet quantity: 10/pallet



Modern trendy office chair with open backrest shell



Seat height adjustable in various positions by safety gaslift



Newly designed backrest « Window » with breathable mesh cover which provides a pleasant „fool-good climate“ at the back




Backrest height adjustable for an optimal adaption to the body size



Special pelvic seat for an optimal support of the pelvic area, with rounded front edge (bolster for knees), with seat depth adjustment approx.. 5-6 cm (sliding seat)



New synchro-mechanism with extra wide opening angle, for the synchronous adjustment of the seat- and backrest angle - seat and backrest follow the body movements, tension individually adjustable to the body weight, lockable in various positions



Extra large and solid polyamide base black or aluminium base polished, equipped with braked double-wheel safety castors suitable for carpet floors



Optional: height adjustable armrests „TW1“, „TW2“ or „TW3“



This product has the GS-sign of the Intertek in Fuerth and complies in this relation to all security requirements

Max. user height 1,92 m | Max. user weight 110 kg | Max. using time / day 8 hours



Open X Deluxe (N)

without sliding seat

Model	Item no.
Polyamide base black, without sliding seat	
without armrests	OX2000
with armrests „TW1(BIG)“, item no. 7111	OX200TW1
with armrests „TW2“, item no. 7157	OX200TW2
with armrests „TW3“, item no. 7161	OX200TW3
Aluminum base polished, without sliding seat	
without armrests	OX2900
with armrests „TW1(BIG)“, item no. 7111	OX290TW1
with armrests „TW2“, item no. 7157	OX290TW2
with armrests „TW3“, item no. 7161	OX290TW3
OPTIONS Hard floor castors big, item no. 6990 / Foot glides high, item no. 6990-2	

Fabrics

Seat: fabric group T (100% Trevira CS)
Backrest: mesh B50 black or B53 white

Seat: fabric group BJ (100% polyester)
Backrest: mesh B50 black or B53 white

Dimensions

Seat height: 42-57 cm
Seat width: 47 cm
Seat depth: 47 cm
Backrest height: 58 cm
Total height: 106-128 cm
Total depth: 56 cm

Technical data

Weight: approx. 18,2 kg
Unit: 1/carton
Pallet quantity: 10/pallet



Modern trendy office chair with open backrest shell



Seat height adjustable in various positions by safety gaslift



Newly designed backrest « Window » with breathable mesh cover which provides a pleasant „fool-good climate“ at the back




Backrest height adjustable for an optimal adaption to the body size



Special pelvic seat for an optimal support of the pelvic area, with rounded front edge (bolster for knees)



New synchro-mechanism with extra wide opening angle, for the synchronous adjustment of the seat- and backrest angle - seat and backrest follow the body movements, tension individually adjustable to the body weight, lockable in various positions



Extra large and solid polyamide base black or aluminium base polished, equipped with braked double-wheel safety castors suitable for carpet floors



Optional: height adjustable armrests „TW1“, „TW2“ or „TW3“



This product has the GS-sign of the Intertek in Fuerth and complies in this relation to all security requirements

Max. user height 1,92 m | Max. user weight 110 kg | Max. using time / day 8 hours